



**CODE 0.525.**

## **interior**

**Washable latex paint for interiors**

---

### **GENERAL PROPERTIES**

INTERIOR is a latex paint developed from innovative formulation criteria. It offers an optimum "whiteness", good hiding power & washability. The special synthetic polymers in emulsion provide a good scrub resistance, ease of application & flow.

These features together with an appealing matt effect make INTERIOR a quality finish for interiors.

EPD® Certification, Environmental Product Declaration in accordance with ISO 14025 and EN 15804.

### **INSTRUCTIONS**

---

#### **Substrate preparation:**

- Bare interior walls: use a soft brush to remove dust & unsound plaster. Level any imperfections (holes, cracks or fissures), with LITOSTUCCO or SILVER STUCK (powder stucco) adding as many times as necessary. Allow 6 hrs, sand the stuccowork & clean accurately. Seal the whole surface with a hand of thinned ISOLEX W or ARDFIX (1 part in 8 parts of water). Allow 4 or 12 hrs respectively & apply 2 hands of INTERIOR.
- Interiors with distemper paintwork: clean accurately & stucco any imperfections with LITOSTUCCO as indicated above. Sand & seal the whole surface with a hand of ISOLEX W or ARDFIX. Allow 12 hrs & apply INTERIOR.
- Interiors with washable latex paintwork: clean accurately, stucco any imperfections, sand & dust. Seal the stucco work with a hand of ARDFIX. Allow 4 hrs & proceed with INTERIOR.

#### **Application:**

Apply INTERIOR as follows:

- Brush: stir well, dilute at 35-40% in water volume & apply by criss-cross brushing. Allow 2-3 hrs & proceed with the second hand thinning INTERIOR at 30-35% in water volume.
- Roller: dilute at 20-25% in water volume.
- Air-spray gun: thin at 10-15% in water volume until roughly 80 DIN/sec viscosity (DIN cup # 4 at 20°C) and apply using 1,5-1,9 mm Ø nozzles - pressure around 3 kg/cm. Allow at least 6 hours between each layer.
- INTERIOR is easy to tint using IDROPAINT 502, high concentration colorants, COLORATUTTO 0.951 & ARDCOLOR 2.950.
- Do not apply at a temperature below +5°C or above +35°C.
- Wash equipment immediately after use with water.
- Store in cool, frost free premises.

- INTERIOR is compatible with the 16COLOURS & WIZARD tinting systems.
- Use products in compliance with the current Health & Safety Regulations. Dispose of spent material/containers according to the same.
- Refer to the PSDS for further details.

## TECHNICAL PROPERTIES

|                      |                        |                                     |
|----------------------|------------------------|-------------------------------------|
| SPECIFIC WEIGHT      |                        | <b>1640 ÷ 50 g/l</b>                |
| VISCOSITY AT 20 °C   |                        | <b>12.500 ± 2000 cP</b>             |
| COLOUR               |                        | <b>White</b>                        |
| DRYING AT 20 °C      | TOUCH DRY              | <b>2 hrs</b>                        |
|                      | THROUGH DRYING         | <b>24 hrs</b>                       |
| WET SCRUB RESISTANCE | EN 13300 (ISO 11998)   | <b>Class 3</b>                      |
| CONTRAST RATION      | EN 13300 (ISO 6504-3)  | <b>Class 2 to 5 m<sup>2</sup>/l</b> |
| GLOSS (85°)          | EN 13300 (EN ISO 2813) | <b>&lt; 5 G.U. Dead Matt</b>        |

## YIELD

A two coat cycle implies a yield of 5 - 5,5 m<sup>2</sup>/l.

## TENDER SPECIFICATION ITEM

### WASHABLE LATEX PAINT

Application on treated surfaces of two layers of highly covering emulsion paint based on synthetic copolymers in aqueous dispersion & colouring pigments type INTERIOR, with a min consumption of 0,19 l/m<sup>2</sup>.

€/m<sup>2</sup>

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide.

Revision 2024/02



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1<sup>a</sup> Strada, 13 – Tel. 049.8060000 (5 linee)  
Fax 049.773749 – [www.ard-raccanello.it](http://www.ard-raccanello.it) - E-mail: [assistenza@ard-raccanello.it](mailto:assistenza@ard-raccanello.it)